

# Product Data Sheet

PAGE 1 Ref. P-L65-R7



# Enviroflex L65 Series

One piece maintenance for peace of mind

## TWICE THE HOSE LIFE AND SIGNIFICANT POWER SAVINGS compared to other Peristaltics\*

### Another World first from Environmental Pumping Solutions

With our Enviroflex L Series pump you get all the benefits of other peristaltic pumps, with the two key additional benefits of a much slower speed for a given flowrate; and rotating rollers for soft hose compression. These two features greatly increase hose life & reduce power consumption.

The L Series pump displaces typically twice the flowrate of our competitors pump and we achieve this by making our pump larger\*. In our design the rollers effective contact with the hose is maximised, producing an increased flow per revolution. This means we can run our pump at about half our competitors speed to produce the same flowrate and hence double the hose life\*.

Our pump uses soft action rotating rollers to compress the hose instead of hard fixed shoes. The advantage of our rollers is that they gently rotate as they compress the hose, losing very little power from surface friction. Fixed shoes by stark comparison apply a large contact area, that drags on the hose surface, creating a high level of wear, friction and hence significant power loss.

The L65's design features will provide you with typically **TWICE the expected hose life and significant power savings** when compared to other peristaltic pumps\*.

### Common Applications

Typical duties include:

- Effluent Processing
- Lime Slurry Transfer
- Mining Waste Transfer
- Mud Slurry Transfer
- Municipal Waste Transfer
- Tailings Transfer
- Thickener Transfer
- And of course many others.

If you need a reliable pump that's easy to maintain, clean and simple to operate, then the **Enviroflex L Series is the one for you.**  
**Just some of our Hose Materials**

- Butyl
- EPDM
- Hypalon
- Natural Rubber
- Neoprene
- Nitrile Rubber



An L65 pump on a pressure test application, chosen due to its high flowrate and low power consumption. As well as saving on power, our low friction rollers dramatically reduce wear on the hose caused by the physical stretch and frictional heat from competitors fixed shoe designs, greatly extending overall hose life.

### Technical Data L65 Series

Weight: 375kg (Varies with Drive)  
Dims: 1067W x 889D x 1134H mm  
Temperature: Max 80 degrees C  
Displacement: 8.19 Litres per rev  
Max continuous speed: 35 rpm  
Max pressure: 10 Barg  
Max cont Flowrate: 0 to 17,200 l/hr  
Standard Connections: 2 1/2" BSP Male

Below is a picture of a recent contract for 48 pumps of various sizes L25 to L100, selected for the applications, because of the L Series high flow per revolution and longer hose life.



### **OPTIONS**

- **FDA Approval on hose material**
- Connections
- Hose failure detection
- Electronically variable speed drive
- Manually variable speed drive
- Global voltages from 200v to 525v
- Exclusive stock program

### Highlights

- **TWICE the hose life and significant power savings when compared to other Peristaltic pumps\***
- *Ideal for corrosive environments with pump casing options in 304 and 316 stainless steel (Standard is carbon steel)*
- *Accurate & controllable flowrate means easy integration with your process requirements*
- *Essentially one wearing part means low maintenance and low spares inventory*
- *Excellent solids/sludge handling with no valves or balls to stick*
- *Self Priming suction lift up to a maximum of 9.5m vertical*
- *Fixed and variable speed options*



Environmental Pumping Solutions Ltd

[www.environmentalpumping.co.uk](http://www.environmentalpumping.co.uk)

UK Tel: 0800 0180 007

UK Fax: 0870 8730282

Int'l Tel: +44 (0) 1635 576028

Int'l Fax: +44 (0) 1189 657783

The information contained in this document is believed to be correct but neither Environmental Pumping Solutions nor its distributors accept any liability for any errors or omissions and reserves the right to alter any specifications without notice.

Copyright 2006-2010. All rights reserved.

\*Typical figures call for exact data.